




28 TRAY / 130 SQ. FT COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



99 Hour
Timer



30-90°
Precision
Thermostats



Glass
Observation
Window



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

28CUD SPECIFICATIONS

Max Power Usage	6 kW (3 kW x 2 Zones)	Total Tray Area	130 sq. ft
Avg Power Usage	2.4 kW (1.2 kW x 2 Zones)	Total Trays	28
Voltage / Frequency	200-240V/50-60Hz	Tray Dimensions	20" x 33.5"
Max Amperage	29A	Space Between Trays	2"
Safety Breaker Required	Single Phase/32A	Tray Mesh Spacing	1/2" x 1/2"
Temperature Range	Ambient Mode, 85 - 195°F	Machine Weight	310 lbs
Timer	0 - 99hr	Product Dimensions (W x H x D)	2' 10.5" x 5' 6.5" x 2' 2.5"
Independent Zones	2	Features	Memory Function, Ambient Air Mode
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminum door handle; Tempered glass observation window; Control Panel with PVC finish.		