60 Tray commercial food dehydrator





Model: 60-CUD

Commercial Use

Product specification

Economical X-Large Capacity

1 Todact specification			
Max Power Usage Avg. Power Usage	4.5 kW (1.5 kW x 3 Zones) 1.8 kW (600 W x 3 Zones)	Total Tray Area	107 sq. ft
Voltage / Frequency	200-240V/50-60Hz	Total Trays	60
Max Amperage	19.56A	Tray Dimensions	16" x 16"
Safety Breaker Required	Single Phase/25A	Space Between Trays	1 2/5"
Temperature Range	Ambient Mode, 85 - 195°F	Tray Mesh Spacing	5/16" x 5/16"
Timer	0 - 99hr	Machine Weight	190 lbs
Features	Memory Function, Ambient Air Mode	Product Dimensions (W x H x D)	4' 7.5" x 3' .5" x 22"
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminum door handle; Tempered glass observation window; Control Panel with PVC finish.		



60 floor

capacity



5750 W

Frequency

Energy Saving

 ϵ

Certification



Adjustable Horizontal time and hot air temperature



Stainless Steel Case



Stainless Steel Frame





VIEW IN AUGMENTED REALITY

Scan the following QR code to view this machine in your warehouse / kitchen environment.

*iPhone 7 or newer required