

# G 160A HC USA

## Daily production up to 399 lb Features & Plus

- Granular ice - 80-82% dry
- 1l (water) - 1kg (ice)
- AISI 304 SS Scotch Brite finish
- AISI 304 SS evaporator
- Air cooling system
- Easy cleanable internal rounded surfaces
- HCFC-Free insulated storage
- Dust-proof water basin
- RoHS Free
- Disappearing insulated door
- Electromechanical operation
- ON-OFF rocker switch
- Automatic water charge
- HFC Free

HC  
R290

1L  
1kg

AISI  
304

+43°  
VLT

Energy  
Class

+


NO  
DUST

RoHS  
FREE

+

ON  
OFF

HC  
R290



## Technical information

Production 24h*	368 lb
Cooling system	A
Refrigerant	R290
Average power consumption**	665 W
Net weight	139 lb
Gross weight	163 lb
Fuse	10 A

Water consumption

12,0 gal/100 lbs

Sizes (WxDxH) \*

22" - 22 6/16" - 23 10/16"

Sizes with pack (WxDxH)

25 6/16" - 25 6/16" - 31 14/16"

Finish

AISI 304 Stainless Steel, Scotch Brite

- ① Water in: 3 3/16" - 4 12/16" - 3/4"
- ② Water out: 18 14/16" - 2 9/16" - 15/16"
- ③ Electrical connections: 2 11/16" - 11 7/16"



Installation

Standard Voltage 115 V ~ 60 Hz

\* Ambient temperature +90° F - Water temperature +70° F | \*\* Ambient temperature +109° F