

Project Name:	
Location:	
Item #:	Qty:
Model:	

## **ECONOMY REACH-IN FREEZER**

MODEL: MXX-23FHC



MXX-23FHC

#### **ELECTRIC** -

115V / 60Hz / 1Ph (230V / 50-60Hz / 1Ph is available as an option) 6' (2m) NEMA 5-15P cord set inculded



#### **3RD PARTY APPROVALS**









Certified to ANSI UL 471 Zero Ozone Depletion Potential

## MAXX COLD WARRANTY (USA / CANADA) -

Contact Maxx Cold for warranty statement at TechnicalServices@TheLegacyCompanies.com or 877.368.2797 The Maxx Cold X-Series 23 Cu Ft Single Door Economy Freezer is supplied with 3 heavy-duty adjustable shelves and features a digital solid-state temperature control system with digital display for easy viewing. The energy efficient refrigeration system provides rapid temperature recovery.

#### FEATURES AND CONSTRUCTION —

- Easy to clean, low maintenance white painted steel exterior and white painted aluminum interior
- Field-reversible hinged door with heavy-duty recessed fulllength handle
- Door lock & key set for security
- Three (3) adjustable wire shelves, one (1) fixed half shelf
- Equipped with 2.5" swivel casters
- Digital control system
- LED temperature display
- Automatic defrost system
- Door frame heaters
- Easy to clean/replace removable snap-in gaskets
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Front-breathing bottom-mounted condensing unit
- Urethane foam insulated walls

MXX-23FHC ...... 23 Cu Ft (651 L)


#### TEMPERATURE ———

Holding temperature ......-10°F to 10°F (-23°C to -12°C)


Oversized refrigeration system delivers rapid temperature recovery

# **ECONOMY REACH-IN FREEZER**


MXX-23FHC







SIDE VIEW



MODEL	EXTERNAL Dimensions	INTERNAL Dimensions	NOMINAL Capacity	HOLDING Temperature Range	AMP Draw	SHIPPING WEIGHT	REFRIGERANT And Charge Size	DOORS / Shelves	ELECTRICAL
MXX-23FHC	30.6" x 29" x 78" (777 x 737 x 1981 mm)	26.3" x 21.6" x 58.9" (668 x 549 x 1496 mm)	23 Cu Ft (651 L)	-10°F to 10°F (-23°C to -12°C)	7.0A	286 lbs (130 kg)	R-290A 4.23oz (120 g)	1/3	115V / 60Hz / 1Ph

## **INSTALLATION** -

• Shorter caster options are available to lower the overall height of the unit